

Package: sfcentral (via r-universe)

September 10, 2024

Title Spatial centrality and dispersion statistics

Version 0.1.0

Date 2020-02-28

Maintainer Gabriel Gaona <gabo@gavg712.com>

Description sfcentral package is a collection of functions for computing centographic statistics (e.g., standard distance, standard deviation ellipse, standard deviation box) for observations taken at point locations in 2D or 3D. The sfcentral library was inspired in aspace package but conceived to be used in a tidy*-sf context, (e.g in `dplyr::groupy_by`, `dplyr::summarise`, `dplyr::mutate`, etc, contexts).

License GPL (>= 3)

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.1

Imports geodist (>= 0.0.7), Hmisc (>= 4.6.0), lwgeom (>= 0.2.0), scales (>= 1.2.0), sf (>= 1.0.8), stats

Suggests ggplot2 (>= 3.3.6), testthat (>= 3.0.0)

Config/testthat/edition 3

Repository <https://gabrielvgaona.r-universe.dev>

RemoteUrl <https://gitlab.com/gavg712/sfcentral>

RemoteRef HEAD

RemoteSha 76729fefa4d1220e73864adc9740bcfa327986cc

Contents

st_central_point	2
st_sd_box	4
st_sd_distance	5
st_sd_ellipse	6
Index	8

st_central_point *Spatial centrality*

Description

Functions to find spatial measures of gravity centers.

Usage

```
st_central_point(.x, .y, ...)
```

```
## S3 method for class 'sfg'
st_central_point(
  .x,
  .y = NULL,
  weights = NULL,
  method = c("mean", "median", "geometric", "feature", "min.dist"),
  ...
)
```

```
## S3 method for class 'sf'
st_central_point(
  .x,
  .y = NULL,
  weights = NULL,
  method = c("mean", "median", "geometric", "feature", "min.dist"),
  ...
)
```

```
## S3 method for class 'sfc'
st_central_point(
  .x,
  .y = NULL,
  weights = NULL,
  method = c("mean", "median", "geometric", "feature", "min.dist"),
  ...
)
```

Arguments

.x, .y	sf points 2D or 3D
...	arguments to be passed to or from other methods
weights	Numeric. Used in for weighed Mean Center. Has to be same length as number of points.
method	Character. Type of center point to calculate
dist	Atomic numeric, Default 100. Starting distance value for center moving during iterations.

Details

Spatial centers are spatial measures of the gravity center.

methods options are: "mean" is the mean center (equivalent to centroid of the points) calculated by the arithmetic mean of each axis; "geometric", is the corresponding geometric mean of each axis; "median", is the median center, a pair of c(median(x), median(y)) coordinates; "feature", is a minimization of the sum of distances from *ith* point to every point; "min.dist", is iterative looking for the closest point in bbox of .x that minimizes the sum of distances from *ith* point to every point in the dataset

Value

"Simple Features" of length 1.

Note

Inspired on `aspace::*()` from Ron Buliung & Randy Bui (2012)

Author(s)

Gabriel Gaona

Examples

```
requireNamespace("ggplot2", quietly = TRUE)
library(sf, quietly = TRUE)
library(ggplot2)
bbx <- matrix(c(697047,9553483,
               696158,9560476,
               700964,9561425,
               701745,9555358),
             byrow = TRUE,
             ncol = 2)
bbx <- st_multipoint(bbx)
bbx <- st_cast(bbx,"POLYGON")
bbx <- st_sfc(bbx, crs = 31992)
set.seed(1234)
points <- st_sf(geometry = st_sample(bbx, 100))
mean_center <- st_central_point(points, method = "mean")
median_center <- st_central_point(points, method = "median")
geom_center <- st_central_point(points, method = "geometric")
central_feature <- st_central_point(points, method = "feature")
min_dist_center <- st_central_point(points, method = "min.dist")
ggplot() +
  geom_sf(data = points, color = "steelblue", size = 0.5) +
  geom_sf(data = mean_center, color = "blue", size = 3) +
  geom_sf(data = median_center, color = "red") +
  geom_sf(data = geom_center, color = "grey80") +
  geom_sf(data = central_feature, color = "orange") +
  geom_sf(data = min_dist_center, color = "green")
```

 st_sd_box

Standard deviation box calculator in 2D or 3D

Description

Calculate the spatial deviation box from a points sf dataset. #' @author Gabriel Gaona

Usage

```
st_sd_box(.x, centre = NULL, weights = NULL, ...)
```

```
## S3 method for class 'sfg'
```

```
st_sd_box(.x, centre = NULL, weights = NULL, ...)
```

```
## S3 method for class 'sf'
```

```
st_sd_box(.x, centre = NULL, weights = NULL, ...)
```

```
## S3 method for class 'sfc'
```

```
st_sd_box(.x, centre = NULL, weights = NULL, ...)
```

Arguments

.x	sf points 2D or 3D
centre	Numeric. Coordinates 2D or 3D of central point. Default NULL, performs a calculation of mean_centre() from point localities
weights	Numeric. Same length of number of .x.
...	ignored

Value

Depends on input, "coords" returns a data.frame of 2 or 3 columns and 4 or 8 point coordinates. "param" returns a data.frame with centre coordinates, standard deviation in each axis, space(area for 2D, volume for 3D) and number of dimensions in coordinates.

Examples

```
requireNamespace("ggplot2", quietly = TRUE)
library(sf, quietly = TRUE)
library(ggplot2)
bbx <- matrix(c(697047,9553483,
               696158,9560476,
               700964,9561425,
               701745,9555358),
             byrow = TRUE,
             ncol = 2)
bbx <- st_multipoint(bbx)
bbx <- st_cast(bbx, "POLYGON")
```

```

bbx <- st_sfc(bbx, crs = 31992)
set.seed(1234)
points <- st_sf(geometry = st_sample(bbx, 100))
SD_BOX <- st_sd_box(points)
ggplot() +
  geom_sf(data = SD_BOX, fill = NA, color = "darkolivegreen") +
  geom_sf(data = points, color = "steelblue", size = 0.5)

```

st_sd_distance	<i>Standard deviation distance calculator</i>
----------------	---

Description

Calculate the spatial deviation distance from a points sf dataset.

Usage

```
st_sd_distance(.x, centre = NULL, weights = NULL, ...)
```

```
## S3 method for class 'sfg'
st_sd_distance(.x, centre = NULL, weights = NULL, ...)
```

```
## S3 method for class 'sf'
st_sd_distance(.x, centre = NULL, weights = NULL, ...)
```

```
## S3 method for class 'sfc'
st_sd_distance(.x, centre = NULL, weights = NULL, ...)
```

Arguments

.x	sf points 2D or 3D
centre	One central point of class <i>sf</i> , <i>sfc</i> , <i>numeric</i> (length 2), <i>matrix</i> (2 col, 1 row), <i>data.frame</i> (2 col, 1 row), or <i>list</i> (length 2). Default NULL, means a calculation of the <code>st_central_point()</code> from .x localities.
weights	Numeric. Same length as number of points in .x.
...	other parameters for <code>sf::st_distance()</code>

Value

A sf "POLYGON" with attributes:

- radius (standard deviation distance)
- area surrounding,
- perimeter,
- center coordinates,
- weighted indicator if weights were used or not in the calculator.

Author(s)

Gabriel Gaona

Examples

```

requireNamespace("ggplot2", quietly = TRUE)
library(sf, quietly = TRUE)
library(ggplot2)
bbx <- matrix(c(697047,9553483,
               696158,9560476,
               700964,9561425,
               701745,9555358),
             byrow = TRUE,
             ncol = 2)
bbx <- st_multipoint(bbx)
bbx <- st_cast(bbx,"POLYGON")
bbx <- st_sfc(bbx, crs = 31992)
set.seed(1234)
points <- st_sf(geometry = st_sample(bbx, 100))
SDD <- st_sd_distance(points)
ggplot() +
  geom_sf(data = SDD, fill = NA, color = "darkolivegreen") +
  geom_sf(data = points, color = "steelblue", size = 0.5)

```

st_sd_ellipse

Standard deviation ellipse calculator

Description

Calculate the spatial deviation ellipse from a points sf dataset.

Usage

```

st_sd_ellipse(.x, centre = NULL, weights = NULL, ...)

## S3 method for class 'sfg'
st_sd_ellipse(.x, centre = NULL, weights = NULL, ...)

## S3 method for class 'sf'
st_sd_ellipse(.x, centre = NULL, weights = NULL, ...)

## S3 method for class 'sfc'
st_sd_ellipse(.x, centre = NULL, weights = NULL, ...)

```

Arguments

.x sf points 2D or 3D

centre	Numeric. Coordinates 2D of central point. Default NULL, performs a calculation of mean_centre() from point localities
weights	Numeric. Same length of number of points.
...	ignored

Value

simple features as "POLYGON" with attributes: centre coordinates, values for mayor and minor axis radius (sigma.x and sigma.y), rotation (theta and theta_corrected) and geometry properties (eccentricity, area and perimeter)

Author(s)

Gabriel Gaona

Examples

```
requireNamespace("ggplot2", quietly = TRUE)
library(sf, quietly = TRUE)
library(ggplot2)
bbx <- matrix(c(697047,9553483,
               696158,9560476,
               700964,9561425,
               701745,9555358),
             byrow = TRUE,
             ncol = 2)
bbx <- st_multipoint(bbx)
bbx <- st_cast(bbx,"POLYGON")
bbx <- st_sfc(bbx, crs = 31992)
set.seed(1234)
points <- st_sf(geometry = st_sample(bbx, 100))
SDE <- st_sd_ellipse(points)
ggplot() +
  geom_sf(data = SDE, fill = NA, color = "darkolivegreen") +
  geom_sf(data = points, color = "steelblue", size = 0.5)
```

Index

sf, 5
sf::st_distance(), 5
st_central_point, 2
st_central_point(), 5
st_sd_box, 4
st_sd_distance, 5
st_sd_ellipse, 6